

CERTIFICATE OF ANALYSIS

Standard product specification

Alkyd Resin (Medium Oil, Soybean)

Formulated product · 60% Solids in Xylene

1. PRODUCT IDENTITY

Product name	Alkyd Resin (Medium Oil, Soybean)
C.A.S. number	Applicable to blend — on request
Grade / standard	60% Solids in Xylene
Description	Viscous amber liquid
Product group	Resins & Binders
Category	Paint, Ink & Coating Chemicals
Country of origin	India
Packing	Bags, drums, carboys, IBC or ISO tank as applicable — customer-specified packing available
Storage	Cool, dry, well-ventilated place in tightly closed original packing

2. ANALYTICAL SPECIFICATION

S. NO.	TEST PARAMETER	SPECIFICATION	TYPICAL RESULT	METHOD
1	Description	Viscous amber liquid	Complies	Visual
2	Assay	Not less than 60.0 % w/w	60.45	Titrimetry / Instrumental
3	Non-volatile Content (Solids)	As per specification	38.7 % w/w	Gravimetry / ASTM D1644
4	Viscosity at 25 °C	As per specification	2459 cP	Brookfield viscometry
5	pH (as supplied)	As per specification	5.1	Potentiometry
6	Density at 25 °C	As per specification	0.983 g/mL	ASTM D1475
7	Heavy Metals (as Pb)	Not more than 20 ppm	Less than 10 ppm	ICP-OES

3. DECLARATION

This document sets out the standard specification for Alkyd Resin (Medium Oil, Soybean) and applies to all consignments of this product and grade supplied by Scapex Exports Pvt. Ltd. It is not a lot-specific release document; a lot-specific certificate carrying the analysis of the material actually shipped is issued with, and travels with, each consignment. Scapex Exports supplies against customer-specified assay limits and pharmacopoeial standards — send your specification sheet and we confirm compliance in writing before the order is accepted.



Scapex Exports Pvt. Ltd. · Ahmedabad, Gujarat, India · info@scapexexports.com · +91 9925522674 — system-generated document, valid without physical signature.