

CERTIFICATE OF ANALYSIS

Standard product specification

Aromatic Rubber Process Oil

Formulated product · Viscosity 1000–1500 cSt

1. PRODUCT IDENTITY

Product name	Aromatic Rubber Process Oil
C.A.S. number	Applicable to blend — on request
Grade / standard	Viscosity 1000–1500 cSt
Description	Dark brown viscous liquid
Product group	Processing Chemicals
Category	Plastic & Rubber Chemicals
Country of origin	India
Packing	Bags, drums, carboys, IBC or ISO tank as applicable — customer-specified packing available
Storage	Cool, dry, well-ventilated place in tightly closed original packing

2. ANALYTICAL SPECIFICATION

S. NO.	TEST PARAMETER	SPECIFICATION	TYPICAL RESULT	METHOD
1	Description	Dark brown viscous liquid	Complies	Visual
2	Non-volatile Content (Solids)	As per specification	53.2 % w/w	Gravimetry / ASTM D1644
3	Viscosity at 25 °C	As per specification	2727 cP	Brookfield viscometry
4	pH (as supplied)	As per specification	6.3	Potentiometry
5	Density at 25 °C	As per specification	1.079 g/mL	ASTM D1475
6	Heavy Metals (as Pb)	Not more than 20 ppm	Less than 10 ppm	ICP-OES

3. DECLARATION

This document sets out the standard specification for Aromatic Rubber Process Oil and applies to all consignments of this product and grade supplied by Scapex Exports Pvt. Ltd. It is not a lot-specific release document; a lot-specific certificate carrying the analysis of the material actually shipped is issued with, and travels with, each consignment. Scapex Exports supplies against customer-specified assay limits and pharmacopoeial standards — send your specification sheet and we confirm compliance in writing before the order is accepted.



Scapex Exports Pvt. Ltd. · Ahmedabad, Gujarat, India · info@scapexexports.com · +91 9925522674 — system-generated document, valid without physical signature.